

HYDRO'K



MANUFACTURING & MACHINE TOOLS



Multipurpose oil

APPLICATIONS

A versatile hose for industrial use.

For diesel oil, mineral oil and grease with aromatic content $\leq 50\%$.

Return hose in hydraulic system and for farming equipment.

Sea water (engine cooling) and aqueous solution.

An allround hose for oil, water, compressed air, grease, etc.

ADVANTAGES

- ┆ A multi-purpose hose to minimize inventory.
- ┆ Ozone, abrasion and oil splash resistant cover.

TECHNICAL DESCRIPTION

Inner tube: oil resistant NBR/PVC, black, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/SBR, black, smooth.

Temperature range: -25°C to $+100^{\circ}\text{C}$.

COMPLEMENTARY INFORMATION

Length 50m: packed in carton.



ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
5.0±0.4	3.25	11.5±0.5	16	48	0.80	30	0.12	20	0060722	☒
5.0±0.4	3.25	11.5±0.5	16	48	0.80	30	0.12	40	0060723	
5.0±0.4	3.25	11.5±0.5	16	48	0.80	30	0.12	80	0060724	☒
5.0±0.4	3.25	11.5±0.5	16	48	0.80	30	0.12	120	0060725	
6.0±0.4	3.5	13.0±0.5	16	48	0.80	35	0.15	20	0060727	☒
6.0±0.4	3.5	13.0±0.5	16	48	0.80	35	0.15	40	0060728	
6.0±0.4	3.5	13.0±0.5	16	48	0.80	35	0.15	80	0060729	
6.0±0.4	3.5	13.0±0.5	16	48	0.80	35	0.15	120	0060730	
8.0±0.5	3.5	15.0±0.6	16	48	0.80	40	0.18	20	0060732	
8.0±0.5	3.5	15.0±0.6	16	48	0.80	40	0.18	40	0060733	
8.0±0.5	3.5	15.0±0.6	16	48	0.80	40	0.18	80	0060734	
8.0±0.5	3.5	15.0±0.6	16	48	0.80	40	0.18	120	0060735	
10.0±0.5	3.5	17.0±0.6	16	48	0.80	45	0.22	20	0060737	
10.0±0.5	3.5	17.0±0.6	16	48	0.80	45	0.22	40	0060738	
10.0±0.5	3.5	17.0±0.6	16	48	0.80	45	0.22	50	0060703	11400
10.0±0.5	3.5	17.0±0.6	16	48	0.80	45	0.22	80	0060739	
10.0±0.5	3.5	17.0±0.6	16	48	0.80	45	0.22	120	0060740	
13.0±0.6	3.75	20.5±0.7	16	48	0.35	50	0.27	20	0060742	
13.0±0.6	3.75	20.5±0.7	16	48	0.35	50	0.27	40	0060743	
13.0±0.6	3.75	20.5±0.7	16	48	0.35	50	0.27	50	0060704	7350
13.0±0.6	3.75	20.5±0.7	16	48	0.35	50	0.27	80	0060744	
13.0±0.6	3.75	20.5±0.7	16	48	0.35	50	0.27	120	0060745	
15.0±0.7	4	23.0±0.8	16	48	0.35	55	0.32	20	0060746	☒
15.0±0.7	4	23.0±0.8	16	48	0.35	55	0.32	40	0060747	
15.0±0.7	4	23.0±0.8	16	48	0.35	55	0.32	80	0060748	
15.0±0.7	4	23.0±0.8	16	48	0.35	55	0.32	120	0060749	
16.0±0.7	4	24.0±0.8	16	48	0.35	60	0.34	20	0060844	☒
16.0±0.7	4	24.0±0.8	16	48	0.35	60	0.34	40	0060845	
16.0±0.7	4	24.0±0.8	16	48	0.35	60	0.34	80	0060846	
19.0±0.7	4.2	27.4±0.8	16	48	0.35	65	0.42	20	0060750	
19.0±0.7	4.2	27.4±0.8	16	48	0.35	65	0.42	40	0060751	
19.0±0.7	4.2	27.4±0.8	16	48	0.35	65	0.42	80	0060753	
25.0±1.0	5	35.0±1.1	16	48	0.35	80	0.68	20	0060755	
25.0±1.0	5	35.0±1.1	16	48	0.35	80	0.68	40	0060756	
25.0±1.0	5	35.0±1.1	16	48	0.35	80	0.68	80	0060757	

Tolerance on length: ±1% (ISO 1307 Standard).

☒ Upon availability.

Digital version



TRELLEBORG

WWW.TRELLEBORG.COM/FLUIDHANDLING