



Blanking Plug for Tube Ends Type FI-VSK ▪ Series L / S



Ordering Codes

FI-VSK-10*L*-W3*-MS

* Blanking Plug for Tube Ends		FI-VSK
* Outside Tube Diameter D1 (in mm)	-10	
* Series	Light Series Heavy Series	L S
* Material Code	Steel, zinc/nickel-plated	-W3
Please contact STAUFF for alternative materials and surface finishings.		
* Assembling / Kitting	Blanking plug only	—
	Blanking plug supplied with cutting ring and union nut	-MS
	Blanking plug supplied with soft-sealing cutting ring and union nut	-MSV

Connecting Parts

	Cutting Ring Type FI-DS	Page 26
	Soft-Sealing Cutting Ring Type FI-WDDS	Page 27
	Support Sleeve Type FI-VH	Page 28
	STAUFF Form Ring Type FI-AR	Page 30
	Union Nut Type FI-M	Page 31
	37° Flared Tube Fitting Set Type FI-AB	Page 35

Series	Tube OD (mm/in)	PN (part / ps)	Dimensions (mm/in)					Weight (³ g/lbs) ca. per 100 ²	Ordering Codes ³
			L	L1 ¹	L2	S1	S2		
L	6	315	17	22	7	14	14	1,40	FI-VSK-06L-W3
	.24	4568	.55	.87	.28	.47	.55	3,08	
	8	315	17	23	8	17	17	1,93	FI-VSK-08L-W3
	.31	4568	.59	.91	.31	.55	.67	4,24	
	10	315	20	24	9	17	19	2,55	FI-VSK-10L-W3
	.39	4568	.63	.94	.35	.67	.75	5,61	
	12	315	21	25	10	19	22	3,44	FI-VSK-12L-W3
	.47	4568	.67	.98	.39	.75	.87	8,74	
	15	315	20	26	11	24	27	4,90	FI-VSK-15L-W3
	.59	4568	.71	1,02	.43	.94	1,06	10,78	
	18	315	21	28	11,5	27	32	6,80	FI-VSK-18L-W3
	.71	4568	.75	1,10	.45	1,06	1,26	14,96	
	22	160	23	30	13,5	32	36	10,70	FI-VSK-22L-W3
	.87	2320	.83	1,18	.53	1,26	1,42	23,54	
	28	160	23	31	14,5	41	41	15,20	FI-VSK-28L-W3
	1,10	2320	.87	1,22	.57	1,61	1,61	33,44	
	35	160	29	36	14,5	46	50	25,90	FI-VSK-35L-W3
	1,38	2320	.98	1,42	.57	1,81	1,97	56,98	
	42	160	30	39	16	55	60	35,30	FI-VSK-42L-W3
	1,65	2320	1,06	1,54	.63	2,17	2,36	77,66	
S	6	630	17	26	11	17	17	1,80	FI-VSK-06S-W3
	.24	9135	.71	1,02	.43	.55	.67	3,96	
	8	630	17	28	13	17	19	2,16	FI-VSK-08S-W3
	.31	9135	.79	1,10	.51	.67	.75	4,75	
	10	630	20	29	12,5	19	22	3,34	FI-VSK-10S-W3
	.39	9135	.79	1,14	.49	.75	.87	7,35	
	12	630	21	31	14,5	22	24	4,60	FI-VSK-12S-W3
	.47	9135	.87	1,22	.57	.87	.94	10,12	
	14	630	23	34	16	24	27	5,88	FI-VSK-14S-W3
	.55	9135	.94	1,34	.63	.94	1,06	12,94	
	16	400	24	34	15,5	27	30	7,54	FI-VSK-16S-W3
	.63	5800	.94	1,34	.61	1,06	1,18	16,59	
	20	400	28	39	17,5	32	36	12,50	FI-VSK-20S-W3
	.79	5800	1,10	1,54	.69	1,26	1,42	27,50	
	25	400	31	44	20	41	46	21,40	FI-VSK-25S-W3
	.98	5800	1,26	1,73	.79	1,61	1,81	47,08	
	30	400	34	47	20,5	46	50	30,40	FI-VSK-30S-W3
	1,18	5800	1,34	1,85	.81	1,81	1,97	76,20	
38	315	38	54	23	55	60	40,80	FI-VSK-38S-W3	
1,50	4568	1,54	2,13	.91	2,17	2,36	89,76		

¹ Approximate dimension in assembled condition.

² Weight excluding cutting ring and union nut.

³ Standard scope of delivery: Blanking plug only.

