Code number 111.20.189.00

Model code:

Description SNP2NN-/-014-L-N-A6-SA-P1-B7-B5-YY-N-N-/-NNN-N-N

URL https://store.danfoss.com/nl-ps/en/Power-Solution/p/111.20.189.00

Product details

Gross weight 2.8 Kg Net weight 2.8 Kg

Displacement 14 cc 014 Displacement 14 cc

Slash separator Slash
O-Ring, Inside Diameter Slash

Drive gear SAE J498-9T-16/32 SA Splined SAE J498-9T-16/32-Dp Class 1FIT -SC06

Inlet size 20x40xM6

Mark position Std on top-drive gear side N Position Marking standard (on the top in relation to drive gear)

Mark type Std Marking

Mounting flange SAE A seal pilot D82,55+2bolts A6 Flange SAE A, pilot Ø82,55 mm and 2 holes for bolts with seal on pilotdiameter (BAW)

Outlet size 15x35xM6 B5 15x35xM6

Ports position Bx-Bx+SAE A-Off-set cover side YY Port type Bx-Bx for flange SAE-A as per catalogue (inverted std. position from flange to cover) LCX

В7

N

20x40xM6

Standard Marking

Standard Version of Project

 Product group
 Aluminium Gear Pumps

 Project version
 Standard Version of Project
 N

 Rear cover
 Standard cover for pump
 P1
 Standard cover for pump

 Rotation
 Left rotation
 L
 Product with counter-clockwise rotation

 Screws
 Screws standard
 N
 Screws standard

 Seals
 Standard seal
 N
 Standard seal

Single Stage Family Gr2 Pump SNP2NN

Type Aluminum Gear Pumps - Group 2

Valve setting without setting NNN without setting

Pricing

List price Currency

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice.

This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.