Code number	111.20.214.00
	Model code:
Description	SNP2NN-/-6,0-R-N-01-BA-P1-C3-C3-NN-N-N-/-NNN-N-N
URL	https://store.danfoss.com/nl-ps/en/Power-Solution/p/111.20.214.00

Gross weight	2.4 Kg		
Net weight	2.4 Kg		
Displacement	Displacement 6,0cc	6,0	Displacement 6,0 cc
Slash separator	Slash	/	
D-Ring, Inside Diameter	Slash	/	
Drive gear	Taper 1:8-M12x1,25-Key=4	BA	Taper 1:8 - M12 x 1,25 - Key = 4 $CO01$
nlet size	13,5x30xM6	C3	13,5x30xM6
Mark position	Std on top-drive gear side	Ν	Position Marking standard (on the top in relation to drive gear)
Mark type	Std Marking	Ν	Standard Marking
Mounting flange	Pilot D36,5 + 4 holes x bolts	01	Flange with pilot Ø36,5 mm and 4 holes for bolts
Dutlet size	13,5x30xM6	C3	13,5x30xM6
Ports position	Standard from catalogue	NN	Standard from catalogue
Product group	Aluminium Gear Pumps		
Project version	Standard Version of Project	Ν	Standard Version of Project
Rear cover	Standard cover for pump	P1	Standard cover for pump
Rotation	Right rotation	R	Product with clockwise rotation
Screws	Screws standard	N	Screws standard
Seals	Standard seal	Ν	Standard seal
Single Stage Family	Gr2 Pump	SNP2N	JN .
Гуре	Aluminum Gear Pumps - Group 2		
Valve setting	without setting	NNN	without setting

Pricing

List price Currency

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice.

This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.