Model code/ Name	GEAR PUMP GR2 FIXED DISPL
Code number	111.20.359.00
	Model code:
Description	SNP2NN-/-6,0-L-N-A6-SA-P1-E6-E5-NN-N-N-/-NNN-N-N
URL	https://store.danfoss.com/nl-ps/en/Power-Solution/GEAR-PUMP-GR2-FIXED-DISPL/p/111.20.359.00

iross weight	2.35 Kg		
let weight	2.35 Kg		
Displacement	Displacement 6,0cc	6,0 Displacement 6,0 cc	
lash separator	Slash	/	
-Ring, Inside Diameter	Slash	/	
Drive gear	SAE J498-9T-16/32	SA Splined SAE J498-9T-16/32-Dp Class 1FIT -SC06	
nlet size	1-1/16-12UN	E6 1-1/16-12UN	
fark position	Std on top-drive gear side	N Position Marking standard (on the top in relation to drive gear)	
Iark type	Std Marking	N Standard Marking	
Iounting flange	SAE A seal pilot D82,55+2bolts	A6 Flange SAE A, pilot Ø82,55 mm and 2 holes for bolts with seal on pilotdi	umeter (BAW)
Outlet size	7/8-14UNF	E5 7/8-14UNF	
orts position	Standard from catalogue	NN Standard from catalogue	
roduct group	Aluminium Gear Pumps		
roject version	Standard Version of Project	N Standard Version of Project	
lear cover	Standard cover for pump	P1 Standard cover for pump	
otation	Left rotation	L Product with counter-clockwise rotation	
crews	Screws standard	N Screws standard	
eals	Standard seal	N Standard seal	
ingle Stage Family	Gr2 Pump	SNP2NN	
ype	Aluminum Gear Pumps - Group 2		
alve setting	without setting	NNN without setting	

Pricing List price

Currency

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice.

This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.