Model co	ode/ Name	GEAR MOTOR GR2 BIDIRECT FIXED DISPL
Code nui	mber	121.20.098.00
		Model code:
Descripti	ion	SNM2NN-/-8,0-B-N-06-SA-M6-E5-E5-NN-N-N-/-NNN-N-N
		https://store.danfoss.com/nl-ps/en/Power-Solutions/Motors/Mobile-motors/Gear-motors/GearMe-aluminum-gear-motors/GEAR-MOTOR-GR2-
URL		BIDIRECT-FIXED-DISPL/p/121.20.098.00

	Product details			
	Gross weight	2.45 Kg		
	Net weight	2.45 Kg		
	Displacement	Displacement 8,0cc	8,0	Displacement 8,0 cc
	Slash separator	Slash	/	
	O-Ring, Inside Diameter	Slash	/	
	Drive gear	SAE J498-9T-16/32	SA	Splined SAE J498-9T-16/32-Dp Class 1FIT -SC06
	Inlet size	7/8-14UNF	E5	7/8-14UNF
	Mark position	Std on top-drive gear side	Ν	Position Marking standard (on the top in relation to drive gear)
	Mark type	Std Marking	Ν	Standard Marking
	Mounting flange	SAE A pilot D82,55+2 bolts	06	Flange SAE A, pilot Ø82,55 mm and 2 holes for bolts
	Outlet size	7/8-14UNF	E5	7/8-14UNF
	Ports position	Standard from catalogue	NN	Standard from catalogue
	Product group	Aluminium Gear Motors		
	Project version	Standard Version of Project	Ν	Standard Version of Project
	Rear cover	Cover M+drain 9/16-18UNF-2B	M6	Standard cover for motor drain 9/16-18UNF-2B
	Rotation	Bidirectional	В	Bidirectional
	Screws	Screws standard	Ν	Screws standard
	Seals	Standard seal	Ν	Standard seal
Single Stage Family Gr2 Bidir.Motor		Gr2 Bidir.Motor	SNM2N	N
	Туре	Aluminum Gear Motors - Group 2		
	Valve setting	without setting	NNN	without setting

Pricing List price

Currency

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice.

This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.