Code number	111.20.055.00
	Model code:
Description	SNP2NN-/-019-R-N-02-AA-P1-B7-B5-NN-N-N-/-NNN-N-N
URL	https://store.danfoss.com/nl-ps/en/Power-Solution/p/111.20.055.00

Bross weight	3 Kg		
let weight	3 Kg		
Displacement	Displacement 19cc	019	Displacement 19 cc
lash separator	Slash	/	
O-Ring, Inside Diameter	Slash	/	
Drive gear	Taper 1:5-M12x1,25-Key3	AA	Taper 1:5 - M12 x 1,25 - Key = 3 CO02
nlet size	20x40xM6	B7	20x40xM6
Aark position	Std on top-drive gear side	N	Position Marking standard (on the top in relation to drive gear)
/lark type	Std Marking	N	Standard Marking
Aounting flange	Pilot D80 + 4 bolts	02	Flange with pilot Ø80 mm and 4 holes for bolts
Dutlet size	15x35xM6	В5	15x35xM6
orts position	Standard from catalogue	NN	Standard from catalogue
roduct group	Aluminium Gear Pumps		
roject version	Standard Version of Project	N	Standard Version of Project
lear cover	Standard cover for pump	P1	Standard cover for pump
Rotation	Right rotation	R	Product with clockwise rotation
crews	Screws standard	N	Screws standard
eals	Standard seal	N	Standard seal
Single Stage Family	Gr2 Pump	SNP2N	IN
уре	Aluminum Gear Pumps - Group 2		
/alve setting	without setting	NNN	without setting

Pricing

List price Currency

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice.

This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.