Code number	111.20.261.00
	Model code:
Description	SNP2NN-/-011-L-N-01-DA-P1-C3-C3-NN-N-N-/-NNN-N-N
URL	https://store.danfoss.com/nl-ps/en/Power-Solution/p/111.20.261.00

Bross weight	2.546 Kg		
Jet weight	2.546 Kg		
Displacement	Displacement 11cc	011	Displacement 11 cc
lash separator	Slash	/	
-Ring, Inside Diameter	Slash	/	
Drive gear	Spline DIN5482 B17x14x10	DA	Spline DIN 5482 B17 x 14 L=10 SC01
nlet size	13,5x30xM6	C3	13,5x30xM6
Aark position	Std on top-drive gear side	N	Position Marking standard (on the top in relation to drive gear)
/lark type	Std Marking	N	Standard Marking
Aounting flange	Pilot D36,5 + 4 holes x bolts	01	Flange with pilot Ø36,5 mm and 4 holes for bolts
Dutlet size	13,5x30xM6	C3	13,5x30xM6
orts position	Standard from catalogue	NN	Standard from catalogue
roduct group	Aluminium Gear Pumps		
roject version	Standard Version of Project	N	Standard Version of Project
lear cover	Standard cover for pump	P1	Standard cover for pump
Rotation	Left rotation	L	Product with counter-clockwise rotation
crews	Screws standard	N	Screws standard
eals	Standard seal	N	Standard seal
ingle Stage Family	Gr2 Pump	SNP2N	N
уре	Aluminum Gear Pumps - Group 2		
alve setting	without setting	NNN	without setting

Pricing

List price Currency

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice.

This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.